

LIGHT LIQUID SEPARATOR ECODEPUR[®] OILTECH NS10

TECHNICAL INFORMATION

ECODEPUR[®] OILTECH NS10 is Light Liquid Separator destined to clean water polluted with light free floating liquids such as engine oils, gas, oil etc, Class 1 in according of EN 858, with double coalescent cell and automatic closure device.




ECODEPUR[®] DEPUROIL[®] Separators has CE marking, in accordance with the legal obligations that stems from the entry into force of the Regulation (UE) N.º 305/2011 of Construction Products, fulfilling all the requisites of the European Standard EN 858-1:2002.

EUROPEAN STANDARD	EN 858-1
EQUIPMENT IDENTIFICATION	Light Liquid Separator
MARCA	ECODEPUR [®]
TYPE	OILTECH NS10
CLASS EN 858-1	Class 1 (<5,0 mg "Mineral Oils"/l ⁽¹⁾)
NOMINAL SIZE	10 l/s
COALESCENT CELL	Double (lamellar/fibrillar)
AUTOMATIC CLOSURE DEVICE	Included (system always calibrated)
VOLUME PRE-SLUDGE TRAP	830 l
OIL STORAGE	1.620 l
FIRE CLASS REACTION	F
MATERIAL	Polyethylene
VENTE POINT	Included (1 1/2")
COVER	Polyethylene

(1) Teste conditions EN 858-1

(2)



TYPE	NS (l/s)	VOLUME (l)	L (mm)	I (mm)	H (mm)	He (mm)	Hs (mm)	C (mm)	Ø PIPE (mm)
OILTECH NS 10	10,0	2.410	2.580	960	1.230	880	770	750 X 1.415	160

TECHNICAL NOTE: In washing areas, the use of hydrocarbon separators, such as ECODEPUR[®] DEPUROIL[®], is recommended.